



Stahlwille 55 34

STAHWILLE®



Popis produktu:

Nástrčná hlavice DIN 3124/ISO 2725-1, ASME B 107.5 M, AS-pohon a HPQ®-Ocel vysoké kvality do 38 mm, chromovaná.

Technická data:

Označení: 55 34

Obj. číslo: 5010034

| Číslo | A mm | d ₁ mm | d ₂ mm | d ₃ mm | L mm | t ₁ mm | t ₂ mm | R g | S |
|-------|------|-------------------|-------------------|-------------------|------|-------------------|-------------------|------|---|
| 55 19 | 19 | 28,5 | 34,7 | 17 | 50 | 16 | 26 | 183 | 5 |
| 55 21 | 21 | 31 | 34,7 | 18 | 50 | 16 | 26 | 226 | 5 |
| 55 22 | 22 | 32 | 34,7 | 19 | 51 | 17 | 25,2 | 199 | 5 |
| 55 24 | 24 | 34 | 34,7 | 21 | 51 | 18,5 | 24,6 | 200 | 5 |
| 55 27 | 27 | 38,5 | 38 | 24 | 54 | 20 | 26,8 | 263 | 5 |
| 55 32 | 32 | 44,5 | 38 | 29 | 58 | 22 | 33 | 326 | 2 |
| 55 33 | 33 | 46 | 40 | 30 | 60 | 22 | 34,7 | 372 | 2 |
| 55 34 | 34 | 47 | 40 | 31 | 60 | 24 | 34,4 | 363 | 2 |
| 55 38 | 38 | 52 | 40 | 35 | 64 | 30 | 37,3 | 429 | 2 |
| 55 41 | 41 | 55,5 | 40 | 33 | 67 | 30 | 37,5 | 498 | 2 |
| 55 46 | 46 | 61 | 40 | 33 | 73 | 34 | 43,5 | 605 | 1 |
| 55 50 | 50 | 66 | 40 | 33 | 80 | 34 | 48,5 | 769 | 1 |
| 55 55 | 55 | 72 | 45 | 33 | 80 | 36 | 49,5 | 954 | 1 |
| 55 60 | 60 | 78 | 45 | 33 | 80 | 40 | 50,5 | 1025 | 1 |

Pro více informací nás neváhejte kontaktovat

KAVON CZ s.r.o. | Medlešice 139, 538 31 Medlešice | info@kavon.cz | +420 466 797 511

WWW.KAVON.CZ