



Stahlwille TORSIOTRONIC 1,2



Popis produktu:

· indicating and click-type · integrated ratcheting bit-holder with 80 teeth that provide a particularly small ratchet angle of only 4.5° and thus enable particularly sensitive working - ideal for hard-to-reach fasteners · after the tool trips, the slip mechanism prevents the preset tightening torque from being inadvertently exceeded, which protects against overtightening · clear display of all the relevant information in a bright, battery-saving colour OLED display - readable at almost any angle · visual assessment of the torqueing action by means of the traffic light colours in the display and laterally placed LEDs · display in a number of languages · long-lasting battery charge with battery-saving stand-by mode. The rechargeable batteries can be quickly and easily changed. · stores up to 2500 fasteners and sequences for reading out and documenting on the PC later by means of the integrated micro-USB interface · the target torque and tolerances can be individually set to evaluate the readings · easy learning curve thanks to almost self-explanatory controls and an easily understood menu structure · three operating modes (first peak, track, peak hold) · tactile, visual and acoustic trigger signals. · the ergonomically designed convex handle promotes strain-free working and is resistant to oils, grease, fuels, brake fluids and Skydrol · clockwise and anticlockwise operation · with 1/4" male square drive (6.3 DIN 3120/ISO 1174-1) for 1/4" sockets · with 1/4" female square drive in the handle end (6.3 DIN 3120/ISO 1174-1) for attaching a 1/4" T-bar · units of measure: cN·m, N·m, ft·lb, in·lb, in·oz · included in the set: SENSOMASTER 4 software, USB cable, bit holder, T-bar handle (size 10) · supplied with 3.6 V lithium battery, type 18650, packaged according to UN 3480 · patented · certificate in accordance with DIN EN ISO 6789-2:2017 · in robust plastic case · display deviation value $\pm 4\%$

Technická data:

Označení: TORSIOTRONIC 1,2

Obj. číslo: 96510712

Číslo	S _i ze	Weight	L (mm)	Measuring range [2]	Measuring range [3]	Measuring range [1]	Internal hex	Weight with box	Internal hex drive [inches]	Measuring range [4]	Measuring range [5]	Square drive
00 TORSIOTRONIC 10	10	575	317	1-10 N·m	0,7-7,3 ft·lb	100-1000 cN·m	D 6,3	1616	1/4	8,8-88,5 in·lb	141-1417 in·oz	6,3 mm (1/4") 12,5 mm (1/2")
TORSIOTRONIC 1,2	1,2	569	317	0,12-1,2 N·m	0,08-0,885 ft·lb	12-120 cN·m	D 6,3	1494	1/4	1,06-10,7 in·lb	16,9-169,9 in·oz	6,3 mm (1/4")
00 TORSIOTRONIC 3	3	570	317	0,3-3 N·m	0,2-2,3 ft·lb	30-300 cN·m	D 6,3	1502	1/4	2,6-26,6 in·lb	42-425 in·oz	6,3 mm (1/4")
TORSIOTRONIC 6	6	572	317	0,6-6 N·m	0,4-4,4 5 ft·lb	60-600 cN·m	D 6,3	1508	1/4	5,3-53,1 in·lb	84,5-849,5 in·oz	6,3 mm (1/4")

Pro více informací nás neváhejte kontaktovat

KAVON CZ s.r.o. | Medlešice 139, 538 31 Medlešice | info@kavon.cz | +420 466 797 511WWW.KAVON.CZ



NÁŘADÍ PRO PRŮMYSL A ŘEMESLO | MOMENTOVÉ A ŘÍZENÉ UTAHOVÁNÍ
ZÁRUČNÍ A POZÁRUČNÍ SERVIS | AKREDITOVANÁ KALIBRAČNÍ LABORATOŘ
SPECIÁLNÍ MANIPULACE | TECHNOLOGIE FLOWDRILL

Pro více informací nás neváhejte kontaktovat

KAVON CZ s.r.o. | Medlešice 139, 538 31 Medlešice | info@kavon.cz | +420 466 797 511
WWW.KAVON.CZ